



Douce Corporation



Mining Thread Bits



Douce Corporation mining tools and accessories

T38 Thread Bit



Product	Dim	Tip size(mm)		No.of flushing holes		Weight (Kg)	Part-No
	mm	Gauge	Front	Side	Front		
	57	6×11	3×10	2	1	1.6	N57F6
	64	6×12	3×11	1	1	1.6	N64F6
	76	6×12	3×12	2	1	2.4	N76F6
	64	8×10	4×10	2	2	1.8	N64F8
	76	8×12	4×12	2	2	2.6	N76F8
	89	8×14	6×12	2	1	3.3	N89F8
	102	8×14	7×12	2	2	4.7	N102F8
	64	6×12	3×11 1×9	—	3	1.7	N64D6
	70	6×12	3×10 1×10	1	3	2.2	N70D6
	89	6×12	3×12 2×9	—	3	4.3	N89D6
	64	8×10	4×10 1×9	1	4	1.7	N64D8
	70	8×10	4×10 1×9	1	4	2.2	N70D8
	76	8×12	4×11 1×11	1	4	2.7	N76D8
	89	8×12	4×12 2×10	—	4	3.3	N89D8
	102	8×12	4×12 4×10	—	4	4.7	N102F8
	60	8×10	4×9	2	2	1.7	R60D8
	64	8×10	4×10	2	2	2	R64D8
	70	8×11	4×10	2	2	2.4	R70D8
	76	8×12	5×11	2	2	3.2	R76D8
	89	8×12	6×11	—	2	5.8	R89D8
	64	8×10	4×10 1×9	1	4	1.9	R64D8
	70	8×10	4×10 1×9	1	4	2.4	R70D8
	76	8×11	4×11 1×11	1	4	3.3	R76D8
	89	8×12	4×12 2×10	1	4	5.3	R89D8

N= normal R=Retract F=Flat Face D=Drop



T45 Thread Bit

Product	Dim	Tip size(mm)		No.of flushing holes		Weight (Kg)	Part-No
	mm	Gauge	Front	Side	Front		
	70	8×11	4×10	2	2	2.4	N70F8
	76	8×12	4×12	2	2	2.6	N76F8
	89	8×12	6×12	2	2	4.5	N89F8
	102	8×14	7×12	2	2	5.0	N102F8
	115	8×14	8×12	2	2	6.8	N115F8
	64	6×11	3×10	1	3	1.6	N64D6
	70	8×11	4×10	1	4	2.4	N70D8
	76	8×12	4×11	1	4	2.6	N76D8
	89	8×12	4×12	1	4	4.6	N89D8
	102	8×14	4×12	1	4	4.5	N102D8
	70	8×10	4×10	2	2	2.5	R70F8
	76	8×12	5×11	2	2	3.1	R76F8
	80	8×12	6×11	2	2	4.0	R80F8
	89	8×14	6×12	2	2	5.1	R89F8
	102	8×12	7×12	—	2	8.2	R102F8
	70	8×10	4×10	1	4	2.2	R70D8
	76	8×10	4×10	2	4	3.1	R76D8
	89	8×12	4×11	2	2	5.4	R89D8
	102	8×12	4×12	—	4	7.8	R102D8
	115	8×14	4×14	—	4	7.8	R115D8

N= normal R=Retract F=Flat Face D=Drop Center

T51 Thread Bit






Product	Diam (mm)	carbide button		No.of flushing holes		Weight (Kg)	Part-No
		Gauge Button	Front Button	Side	Front		
	76	8×12	4×12	1	2	2.7	N76F8
	89	8×12	6×12	2	2	4.9	N89F8
	102	8×14	6×14	—	2	5.8	N102F8
	115	8×14	5×14	2	4	6.8	N115F8
	127	8×16	9×12	—	2	7.5	N127F8
	89	9×11	6×10	—	2	4.6	N89F9
	102	9×12	7×12	—	3	5.9	N102F9
	115	9×14	8×13	—	3	6.6	N115F9
	127	9×14	8×14	—	3	8.4	N127 F9
	152	9×16	11×14	—	3	11.1	N152 F9
 	89	8×12	6×12	1	4	4.5	N89D8
	102	8×14	6×12	1	4	5.7	N102D8
	115	8×14	8×12	—	4	6.8	N115D8
	127	8×14	8×13	—	4	7.5	N127D8
	140	9×16	13×14	—	3	14.4	N165D9
	152	9×16	13×16	—	3	15.1	N178D9
	89	8×12	6×12	—	2	5.1	R89F8
	102	8×12	7×12	—	2	7.1	R102F8
	115	8×14	8×12	—	2	10.5	R115F8
	127	8×16	8×14	—	2	12.5	R127F8
	89	8×12	6×11	1	2	5.3	R89D8
	102	8×14	7×12	—	4	7.4	R102D8
	115	8×16	6×14	—	2	10.2	R115D8
	127	8×14	8×14	—	4	12.0	R127D8

N= normal R=Retract F=Flat Face D=Drop Center



R32 Thread Bits

Product	Diam	Tip size(mm)		No.of flushing holes		Weight (Kg)	Part-No
	mm	Gauge	Front	Side	Front		
	41	4x9	2x8	2	1	0.54	N41F4
	43	4x9	2x9	2	—	0.55	N43F4
	45	4x11	2x9	2	1	0.6	N45F4
	41	5x9	2x8	1	1	0.5	N41F5
	43	5x10	2x8	1	1	0.6	N43F5
	45	5x11	2x9	2	1	0.8	N45F5
	48	5x11	2x10	2	1	0.9	N48F5
	51	5x11	2x10	2	1	1.1	N51F5
	45	6x9	3x8	1	3	0.8	N45F6
	48	6x9	3x9	1	3	0.9	N48F6
	57	6x11	3x10	1	3	1.3	N57F6
	64	6x12	3x11	2	1	1.6	N64F6
	64	8x10	4x10	2	2	1.6	N64F8
	76	8x11	4x11	2	2	2.8	N76F8
	89	8x12	4x12	—	2	2.9	N89F8
	45	6x9	3x8	1	3	1.0	R45F6
	48	6x10	3x8	1	3	1.1	R48F6
	51	6x10	3x9	1	3	1.4	R51F6
	57	6x10	3x10	1	3	1.6	R57F6
	60	8x10	4x9	1	2	1.7	R60F8
	64	8x10	4x10	—	2	1.9	R64F8
	70	8x10	4x10	2	2	2.2	R70F8

N= normal R=Retract F=Flat Face D=Drop Center

R38 Thread Bit



Product	Diam (mm)	carbide button		No.of flushing holes		Weight (Kg)	Part-No
		Gauge button	Front button	Side	Front		
	57	6×11	3×10	2	1	1.6	N57F6
	64	6×12	3×11	1	1	1.6	N64F6
	76	6×12	3×12	2	1	2.4	N76F6
	64	8×10	4×10	2	2	1.8	N64F8
	76	8×12	4×12	2	2	2.6	N76F8
	89	8×14	6×12	2	1	3.3	N89F8
	102	8×14	7×12	2	2	4.7	N102F8
	64	6×12	4×10	—	3	1.7	N64D6
	70	6×12	4×10	1	3	2.2	N70D6
	89	6×12	5×10	—	3	4.3	N89D6
	102	8×14	6×12	2	1	3.3	N102D8
	64	8×10	5×10	1	4	1.7	N64D8
	70	8×10	5×10	1	4	2.2	N70D8
	76	8×11	5×11	1	4	2.7	N76D8
	89	8×12	6×11	—	4	3.3	N89D8
	102	8×12	8×11	—	4	4.7	N102D8
	60	8×10	4×9	2	2	1.7	R60F8
	64	8×10	4×10	2	2	2	R64F8
	70	8×11	4×10	2	2	2.4	R70F8
	76	8×12	5×11	2	2	3.2	R76F8
	89	8×12	6×11	—	2	5.8	R89F8
	64	8×10	5×10	1	4	1.9	R64D8
	70	8×10	5×10	1	4	2.4	R70D8
	76	8×11	5×11	1	4	3.3	R76D8
	89	8×12	6×11	1	4	5.3	R89D8

N= normal R=Retract F=Flat Face D=Drop Center